

Product

## AXMINSTER LUXURY



Specification (in according to)

EN 1307 - EN 14159

Construction	Axminster carpet - cut pile
Pile Composition	80% Lana 20% Poliammide
Backing	PP/CO/PES
Stitches	± 109136 n/m <sup>2</sup>
Pile Height	± 8.5 mm
Total Height	± 11.3 mm
Total Yarn Weight	± 1920 g/m <sup>2</sup>
Yarn Count	Tex 330x3
Pitch	7
Rows	10
Total Weight (carpet finished)	± 2850 g/m <sup>2</sup>
Roll Width	400 cm
Insulation Impact Noise ΔLw	36 dB
Use Intensity Classification - Commercial	Class 33: Heavy
Reaction to Fire	Surface materials and floor coverings with low flame-spread characteristics: c) floor coverings - Item MED/3.18c
Electrical Behaviour – Body Voltage/Walking Test	≤ 2 kV
Luxury Class	Class LC5
Stairs Suitability	A: Intensive use (commercial)
VOC	Pass

### NOTES

RADICI MARINE reserves the right to update this sales sheet without giving prior notice.

Reaction to Fire: testing standards IMO Res.MSC.307 (88) - (2010 FTP Code) Annex 1 Part 2-5

VOC= full details on regulations and protocols satisfied on demand

### CONTACTS

[www.radicimarine.it](http://www.radicimarine.it)

[info@radicimarine.it](mailto:info@radicimarine.it)

+39 035 0950 231