

Product

WINDSOR FB



Specification (in according to)

EN 1307 - EN 14159

Construction	Wilton carpet face to face - cut pile
Pile Composition	80% New Zealand Wool 20% Polyamid
Backing	Synthetics-Secondary backing: Needled Felt Construction (g/m ² 350)
Stitches	± 102400 n/m ²
Pile Height	± 7 mm
Total Height	± 13 mm
Total Yarn Weight	± 1245 g/m ²
Total Weight (carpet finished)	± 2750 g/m ²
Roll Width	400 cm
Insulation Impact Noise ΔLw	34 dB
Use Intensity Classification - Commercial	Class 32: General
Reaction to Fire	Surface materials and floor coverings with low flame-spread characteristics: c) floor coverings - Item MED/3.18c
Electrical Behaviour – Body Voltage/Walking Test	≤ 2 kV
Luxury Class	Class LC4
Stairs Suitability	A: Intensive use (commercial)
VOC	Pass

NOTES

RADICI MARINE reserves the right to update this sales sheet without giving prior notice.

Reaction to Fire: testing standards IMO Res.MSC.307 (88) - (2010 FTP Code) Annex 1 Part 2-5

VOC= full details on regulations and protocols satisfied on demand

CONTACTS

www.radicimarine.it

info@radicimarine.it

+39 035 0950 231

RADICI PIETRO INDUSTRIES & BRANDS S.p.A. Via Cav. Radici, 19 - 24026 Cazzano Sant'Andrea (BG), Italy