

Product

MONTECARLO



Specification (in according to)

EN 1307 - EN 14159

| | |
|--|--|
| Construction | Tufted carpet 1/8"- cut pile |
| Pile Composition | 90% New Zealand Wool 10% Polyester |
| Backing | Action back |
| Stitches | ± 126000 n/m ² |
| Pile Height | ± 6.3 mm |
| Total Height | ± 9.0 mm |
| Total Yarn Weight | ± 1250 g/m ² |
| Total Weight (carpet finished) | ± 2200 g/m ² |
| Roll Width | 400 cm |
| Insulation Impact Noise ΔLw | 32 dB |
| Use Intensity Classification - Commercial | Class 32: General |
| Reaction to Fire | Surface materials and floor coverings with low flame-spread characteristics: c) floor coverings - Item MED/3.18c |
| Electrical Behaviour – Body Voltage/Walking Test | ≤ 2 kV |
| Luxury Class | Class LC4 |
| Stairs Suitability | A: Intensive use (commercial) |
| VOC | Pass |

NOTES

RADICI MARINE reserves the right to update this sales sheet without giving prior notice.

Reaction to Fire: testing standards IMO Res.MSC.307 (88) - (2010 FTP Code) Annex 1 Part 2-5

VOC= full details on regulations and protocols satisfied on demand

CONTACTS

www.radicimarine.it

info@radicimarine.it

+39 035 0950 231

RADICI PIETRO INDUSTRIES & BRANDS S.p.A. Via Cav. Radici, 19 - 24026 Cazzano Sant'Andrea (BG), Italy