

# RADICI

## marine

Product

**WOOL DECOR**  
(product range)

1250//1400



Specification (in according to)

EN 1307 - EN 14159

Construction	Tufted carpet 1/8"- cut pile printed
Pile Composition	80% New Zealand Wool 20% Polyamid
Backing	Action back
Stitches	± 151200 // 173250 n/m <sup>2</sup>
Pile Height	± 7.0 // 7.3 mm
Total Height	± 9.5 // 10.0 mm
Total Yarn Weight	± 1250 // 1400 g/m <sup>2</sup>
Total Weight (carpet finished)	± 2350 // 2500 g/m <sup>2</sup>
Roll Width	400 cm
Insulation Impact Noise ΔLw	31 // 33 dB
Use Intensity Classification - Commercial	Class 32: General // Class 33: Heavy
Reaction to Fire	Surface materials and floor coverings with low flame-spread characteristics: c) floor coverings - Item MED/3.18c
Electrical Behaviour – Body Voltage/Walking Test	≤ 2 kV
Luxury Class	Class LC4 // LC5
Stairs Suitability	A: Intensive use (commercial)
VOC	Pass

### NOTES

RADICI MARINE reserves the right to update this sales sheet without giving prior notice.

Caption: // nominal value Range min and Range max

Reaction to Fire: testing standards IMO Res.MSC.307 (88) - (2010 FTP Code) Annex 1 Part 2-5

VOC= full details on regulations and protocols satisfied on demand

### CONTACTS

[www.radicimarine.it](http://www.radicimarine.it)

[info@radicimarine.it](mailto:info@radicimarine.it)

+39 035 0950 231

RADICI PIETRO INDUSTRIES & BRANDS S.p.A. Via Cav. Radici, 19 - 24026 Cazzano Sant'Andrea (BG), Italy