

Product

AXMINSTER FB



Specification (in according to) **EN 1307 - EN 14159**

Construction	Axminster carpet - cut pile
Pile Composition	80% Wool 20% Polyamide
Backing	PP/CO/PES-Secondary backing: Synthetic Needled Felt (g/m ² 350)
Stitches	± 108750 n/m ²
Pile Height	± 7.1 mm
Total Height	± 12.7 mm
Total Yarn Weight	± 1415 g/m ²
Yarn Count	Tex 330x2
Pitch	7
Rows	10
Total Weight (carpet finished)	± 2650 g/m ²
Roll Width	400 cm
Insulation Impact Noise ΔLw	36 dB
Use Intensity Classification - Commercial	Class 33: Heavy
Reaction to Fire	Surface materials and floor coverings with low flame-spread characteristics: c) floor coverings - Item MED/3.18c
Electrical Behaviour – Body Voltage/Walking Test	≤ 2 kV
Luxury Class	Class LC5
Stairs Suitability	A: Intensive use (commercial)
VOC	Pass

NOTES

ver. 1.0


RADICI MARINE reserves the right to update this sales sheet without giving prior notice.

Reaction to Fire: testing standards IMO Res.MSC.307 (88) - (2010 FTP Code) Annex 1 Part 2-5

VOC= full details on regulations and protocols satisfied on demand

CONTACTS

 www.radicimarine.it

 +39 035 0950 245