

Product

HAND-TUFTED 100% LANA



Specification (in accordance to) **EN 1307 - EN 14159**

Construction	Hand tufted carpet-cut pile
Pile Composition	100% New Zealand Wool
Backing	PP/CO/PES
Stitches	± 55200 n/m ²
Pile Height	± 10 mm
Total Height	± 12 mm
Total Yarn Weight	± 3000 g/m ²
Total Weight (carpet finished)	± 4500 g/m ²
Roll Width	400 cm
Insulation Impact Noise ΔLw	40 dB
Use Intensity Classification - Commercial	Class 33: Heavy
Reaction to Fire	Surface materials and floor coverings with low flame-spread characteristics: c) floor coverings - Item MED/3.18c
Electrical Behaviour – Body Voltage/Walking Test	≤ 2 kV
Luxury Class	Class LC5
Stairs Suitability	A: Intensive use (commercial)
VOC	Pass

NOTES

ver. 1.1

RADICI MARINE reserves the right to update this sales sheet without giving prior notice.

Reaction to Fire: testing standards IMO Res.MSC.307 (88) - (2010 FTP Code) Annex 1 Part 2-5

VOC= full details on regulations and protocols satisfied on demand

CONTACTS

www.radicimarine.it

+39 035 0950 245

RADICI PIETRO INDUSTRIES & BRANDS S.p.A. Via Cav. Radici, 19 - 24026 Cazzano Sant'Andrea (BG), Italy