

Product

HI DECOR (Geotessile) **900//1100//1300**



(product range)

Specification (in according to) **EN 1307 - EN 14159**

Construction	Tufted carpet 1/10"- cut pile printed
Pile Composition	100% Polyamide 6.6
Backing	Synthetic Needled Felt (g/m ² 350)
Stitches	± 158000 // 185650 // 213300 n/m ²
Pile Height	± 5.3 // 6.0 // 6.3 mm
Total Height	± 10.7 // 11.4 // 11.7 mm
Total Yarn Weight	± 900 // 1100 // 1300 g/m ²
Total Weight (carpet finished)	± 2100 // 2300 // 2500 g/m ²
Roll Width	400 cm
Insulation Impact Noise ΔLw	31 // 33 // 35 dB
Use Intensity Classification - Commercial	Class 33: Heavy
Reaction to Fire	Surface materials and floor coverings with low flame-spread characteristics: c) floor coverings - Item MED/3.18c
Electrical Behaviour – Body Voltage/Walking Test	≤ 2 kV
Luxury Class	Class LC3 // LC4 // LC5
Stairs Suitability	A: Intensive use (commercial)
Treatment Stainadverse 	Yes
VOC	Pass

NOTES

ver. 1.0

RADICI MARINE reserves the right to update this sales sheet without giving prior notice.

Caption: // product range-nominal value

Reaction to Fire: testing standards IMO Res.MSC.307 (88) - (2010 FTP Code) Annex 1 Part 2-5

VOC= full details on regulations and protocols satisfied on demand

CONTACTS

 www.radicimarine.it

 +39 035 0950 245

RADICI PIETRO INDUSTRIES & BRANDS S.p.A. Via Cav. Radici, 19 - 24026 Cazzano Sant'Andrea (BG), Italy