

Product

HI DECOR

900//1100//1300



(product range)

Specification (in according to) **EN 1307 – EN 14159**

Construction	Tufted carpet 1/10"- cut pile printed
Pile Composition	100% Polyamide 6.6
Backing	Action back
Stitches	± 158000 // 185650 // 213300 n/m ²
Pile Height	± 5.3 // 6.0 // 6.3 mm
Total Height	± 8.0 // 8.7 // 8.5 mm
Total Yarn Weight	± 900 // 1100 // 1300 g/m ²
Total Weight (carpet finished)	± 2000 // 2200 // 2340 g/m ²
Roll Width	400 cm
Insulation Impact Noise ΔLw	28 // 30 // 32 dB
Use Intensity Classification - Commercial	Class 33: Heavy
Reaction to Fire	Surface materials and floor coverings with low flame-spread characteristics: c) floor coverings - Item MED/3.18c
Electrical Behaviour – Body Voltage/Walking Test	≤ 2 kV
Luxury Class	Class LC3 // LC4 // LC5
Stairs Suitability	A: Intensive use (commercial)
Treatment Stainadverse	Yes
VOC	Pass

NOTES

ver. 1.2

RADICI MARINE reserves the right to update this sales sheet without giving prior notice.

Caption: // product range-nominal value

Reaction to Fire: testing standards IMO Res.MSC.307 (88) - (2010 FTP Code) Annex 1 Part 2-5

VOC= full details on regulations and protocols satisfied on demand

CONTACTS

 www.radicimarine.it

 +39 035 0950 245

RADICI PIETRO INDUSTRIES & BRANDS S.p.A. Via Cav. Radici, 19 - 24026 Cazzano Sant'Andrea (BG), Italy