


Product

MONTECARLO



Specification (in according to) **EN 1307 - EN 14159**

Construction	Tufted carpet 1/8"- cut pile
Pile Composition	90% New Zealand Wool 10% Polyester
Backing	Action back
Stitches	± 126000 n/m ²
Pile Height	± 6.3 mm
Total Height	± 9.0 mm
Total Yarn Weight	± 1250 g/m ²
Total Weight (carpet finished)	± 2200 g/m ²
Roll Width	400 cm
Insulation Impact Noise ΔLw	32 dB
Use Intensity Classification - Commercial	Class 32: General
Reaction to Fire	Surface materials and floor coverings with low flame-spread characteristics: c) floor coverings - Item MED/3.18c
Electrical Behaviour – Body Voltage/Walking Test	≤ 2 kV
Luxury Class	Class LC4
Stairs Suitability	A: Intensive use (commercial)
Treatment Stainadverse 	Yes
VOC	Pass

NOTES


ver. 1.1


RADICI MARINE reserves the reight to update this sales sheet without giving prior notice.

Reaction to Fire: testing standards IMO Res.MSC.307 (88) - (2010 FTP Code) Annex 1 Part 2-5

VOC= full details on regulations and protocols satisfied on demand

CONTACTS

 www.radicimarine.it

 +39 035 0950 245

RADICI PIETRO INDUSTRIES & BRANDS S.p.A. Via Cav. Radici, 19 - 24026 Cazzano Sant'Andrea (BG), Italy