

Product

WINDSOR SB 32//35//38//40



(product range)

40-9 mm

Specification (in according to) EN 1307 - EN 14159

Construction	Wilton carpet face to face - cut pile
Pile Composition	80% New Zealand Wool 20% Polyamide
Backing	Synthetic
Stitches	± 102400//112000//121600 n/m ² //128000 Windsor 40 40-9mm
Pile Height	± 7 mm // 9 mm for 40-9 mm
Total Height	± 9 mm // 11 mm for 40-9 mm
Total Yarn Weight	± 1245 // 1315 // 1420 // 1580 // 1857 g/m ²
Total Weight (carpet finished)	± 1815 // 1900 // 2015 // 2200 // 2480 g/m ²
Roll Width	400 cm
Insulation Impact Noise ΔLw	30 // 34 dB for 40-9 mm
Use Intensity Classification - Commercial	Class 32: General (Windsor 32) // Class 33: Heavy (Windsor 35-38-40-40 9 mm)
Reaction to Fire	Surface materials and floor coverings with low flame-spread characteristics: c) floor coverings - Item MED/3.18c
Electrical Behaviour – Body Voltage/Walking Test	≤ 2 kV
Luxury Class	Class LC4 (Windsor 32/35/38) // LC5 (Windsor 40/ 40-9 mm)
Stairs Suitability	A: Intensive use-commercial
VOC	Pass

NOTES

ver. 1.0

RADICI MARINE reserves the right to update this sales sheet without giving prior notice. Caption: // nominal value Range min and Range max

Reaction to Fire: testing standards IMO Res.MSC.307 (88) - (2010 FTP Code) Annex 1 Part 2-5

VOC= full details on regulations and protocols satisfied on demand

CONTACTS

www.radicimarine.it

+39 035 0950 245

RADICI PIETRO INDUSTRIES & BRANDS S.p.A. Via Cav. Radici, 19 - 24026 Cazzano Sant'Andrea (BG), Italy