

Product

WINDSOR SB (40)



Specification (in according to) **EN 1307 - EN 14159**

Construction	Wilton carpet face to face - cut pile
Pile Composition	80% New Zealand Wool 20% Polyamide
Backing	Synthetic
Stitches	± 128000
Pile Height	± 7 mm
Total Height	± 9 mm
Total Yarn Weight	± 1580 g/m ²
Total Weight (carpet finished)	± 2200 g/m ²
Roll Width	400 cm
Insulation Impact Noise ΔLw	30 dB
Use Intensity Classification - Commercial	Class 33: Heavy
Reaction to Fire	Surface materials and floor coverings with low flame-spread characteristics: c) floor coverings - Item MED/3.18c
Electrical Behaviour – Body Voltage/Walking Test	≤ 2 kV
Luxury Class	Class LC5
Stairs Suitability	A: Intensive use-commercial
VOC	Pass

NOTES

ver. 1.0


RADICI MARINE reserves the right to update this sales sheet without giving prior notice.

Reaction to Fire: testing standards IMO Res.MSC.307 (88) - (2010 FTP Code) Annex 1 Part 2-5

VOC= full details on regulations and protocols satisfied on demand

CONTACTS

 www.radicimarine.it

 +39 035 0950 245

RADICI PIETRO INDUSTRIES & BRANDS S.p.A. Via Cav. Radici, 19 - 24026 Cazzano Sant'Andrea (BG), Italy