

Product

WOOL DECOR (Geotessile) 1250//1400



(product range)

Specification (in according to) **EN 1307 - EN 14159**

Construction	Tufted carpet 1/8" - cut pile printed
Pile Composition	80% New Zealand Wool 20% Polyamide
Backing	Synthetic Needled Felt (g/m ² 350)
Stitches	± 151200 // 173250 n/m ²
Pile Height	± 7.0 // 7.3 mm
Total Height	± 12.7 // 13.1 mm
Total Yarn Weight	± 1250 // 1400 g/m ²
Total Weight (carpet finished)	± 2450 // 2700 g/m ²
Roll Width	400 cm
Insulation Impact Noise ΔLw	33 // 35 dB
Use Intensity Classification - Commercial	Class 32: General // Class 33: Heavy
Reaction to Fire	Surface materials and floor coverings with low flame-spread characteristics: c) floor coverings - Item MED/3.18c
Electrical Behaviour – Body Voltage/Walking Test	≤ 2 kV
Luxury Class	Class LC4 // LC5
Stairs Suitability	A: Intensive use (commercial)
Treatment Stainadverse 	Yes
VOC	Pass

NOTES

ver. 1.1

RADICI MARINE reserves the right to update this sales sheet without giving prior notice. Caption: // nominal value Range min and Range max

Reaction to Fire: testing standards IMO Res.MSC.307 (88) - (2010 FTP Code) Annex 1 Part 2-5

VOC= full details on regulations and protocols satisfied on demand

CONTACTS

 www.radicimarine.it

 +39 035 0950 245

RADICI PIETRO INDUSTRIES & BRANDS S.p.A. Via Cav. Radici, 19 - 24026 Cazzano Sant'Andrea (BG), Italy